

# ActivityClassValService

Activity Class Value Service  
Contact Info: [hello@helloverb.com](mailto:hello@helloverb.com)  
Version: 1  
BasePath: /int/ifsapplications/projection/v1/ActivityClassValService.svc  
All rights reserved  
<http://apache.org/licenses/LICENSE-2.0.html>

## Access

1. HTTP Basic Authentication

## Methods

[ [Jump to Models](#) ]

### Table of Contents

#### [ActivityClassValues](#)

- [DELETE /ActivityClassValues \(ActivityClassSeq={ActivityClassSeq}, Value='{Value}'\)](#)
- [GET /ActivityClassValues \(ActivityClassSeq={ActivityClassSeq}, Value='{Value}'\)](#)
- [PATCH /ActivityClassValues \(ActivityClassSeq={ActivityClassSeq}, Value='{Value}'\)](#)
- [GET /ActivityClassValues](#)
- [POST /ActivityClassValues](#)

#### [ProjectActivityClassVal](#)

- [GET /ActivityClassValues/IfsApp.ActivityClassValService.ProjectActivityClassVal.Default\(\)](#)

## ActivityClassValues

**DELETE /ActivityClassValues (ActivityClassSeq={ActivityClassSeq}, Value='{Value}')**

Delete entity from ActivityClassValues ( `activityClassValuesActivityClassSeqActivityClassSeqValueValueDelete` )

### Path parameters

**ActivityClassSeq (required)**  
*Path Parameter* — key: ActivityClassSeq

**Value (required)**  
*Path Parameter* — key: Value

### Request headers

### Return type

String

### Example data

Content-Type: application/json

```
" "
```

### Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`

### Responses

202 Accepted [String](#)  
204 No Content [String](#)  
403 Forbidden [String](#)  
404 Not found [String](#)

**GET /ActivityClassValues (ActivityClassSeq={ActivityClassSeq}, Value='{Value}')**

Get entity from ActivityClassValues by key ( `activityClassValuesActivityClassSeqActivityClassSeqValueValueGet` )

### Path parameters

**ActivityClassSeq (required)**  
*Path Parameter* — key: ActivityClassSeq

**Value (required)**  
*Path Parameter* — key: Value

### Query parameters

**\$select (optional)**  
*Query Parameter* — Order items by property values, see [http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec\\_SystemQueryOptionorderby](http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptionorderby)>odata Sorting</a>

### Return type

[ProjectActivityClassVal](#)

### Example data

Content-Type: application/json

```
{
  "Validity" : "Global",
  "Objgrants" : "It is a Text",
  "Description" : "It is a Text",
  "BlockedForUse" : true,
  "ETag" : "It is a Text",
  "Value" : "It is a Text",
  "ActivityClassSeq" : 1,
  "keyref" : "It is a Text",
  "luname" : "It is a Text",
  "ActivityClassId" : "It is a Text"
}
```

#### Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- text/plain

#### Responses

200

response body for entity type ProjectActivityClassVal [ProjectActivityClassVal](#)

202

Accepted [String](#)

204

No Content [String](#)

403

Forbidden [String](#)

404

Not found [String](#)

PATCH /ActivityClassValues (ActivityClassSeq={ActivityClassSeq}, Value=' {Value} ') [Up](#)

Update entity in ActivityClassValues (activityClassValuesActivityClassSeqActivityClassSeqValueValuePatch)

#### Path parameters

**ActivityClassSeq (required)**

*Path Parameter* – key: ActivityClassSeq

**Value (required)**

*Path Parameter* – key: Value

#### Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

#### Request body

body [ProjectActivityClassVal-Update](#) (optional)

*Body Parameter* – request body for updating entity type ProjectActivityClassVal

#### Request headers

#### Return type

[ProjectActivityClassVal](#)

#### Example data

Content-Type: application/json

```
{
  "Validity" : "Global",
  "Objgrants" : "It is a Text",
  "Description" : "It is a Text",
  "BlockedForUse" : true,
  "ETag" : "It is a Text",
  "Value" : "It is a Text",
  "ActivityClassSeq" : 1,
  "keyref" : "It is a Text",
  "luname" : "It is a Text",
  "ActivityClassId" : "It is a Text"
}
```

#### Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- text/plain

#### Responses

200

response body for entity type ProjectActivityClassVal [ProjectActivityClassVal](#)

202

Accepted [String](#)

204

No Content [String](#)

403

Forbidden [String](#)

404

Not found [String](#)

GET /ActivityClassValues [Up](#)

Get entities from ActivityClassValues (activityClassValuesGet)

## Query parameters

### \$top (optional)

*Query Parameter* – Show only the first n items, see [http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec\\_SystemQueryOptiontop](http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptiontop)>OData Paging - Top</a>

### \$skip (optional)

*Query Parameter* – Skip the first n items, see [http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec\\_SystemQueryOptionskip](http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptionskip)>OData Paging - Skip</a>

### \$count (optional)

*Query Parameter* – Include count of items, see [http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec\\_SystemQueryOptioncount](http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptioncount)>OData Count</a>

### \$filter (optional)

*Query Parameter* – Filter items by property values, see [http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec\\_SystemQueryOptionfilter](http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptionfilter)>OData Filtering</a>

### \$orderby (optional)

*Query Parameter* – Order items by property values, see [http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec\\_SystemQueryOptionorderby](http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptionorderby)>OData Sorting</a>

### \$select (optional)

*Query Parameter* – Order items by property values, see [http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec\\_SystemQueryOptionorderby](http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptionorderby)>OData Sorting</a>

## Return type

[inline response 200](#)

## Example data

Content-Type: application/json

```
{
  "value" : [ {
    "Validity" : "Global",
    "Objgrants" : "It is a Text",
    "Description" : "It is a Text",
    "BlockedForUse" : true,
    "ETag" : "It is a Text",
    "Value" : "It is a Text",
    "ActivityClassSeq" : 1,
    "keyref" : "It is a Text",
    "luname" : "It is a Text",
    "ActivityClassId" : "It is a Text"
  }, {
    "Validity" : "Global",
    "Objgrants" : "It is a Text",
    "Description" : "It is a Text",
    "BlockedForUse" : true,
    "ETag" : "It is a Text",
    "Value" : "It is a Text",
    "ActivityClassSeq" : 1,
    "keyref" : "It is a Text",
    "luname" : "It is a Text",
    "ActivityClassId" : "It is a Text"
  } ]
}
```

## Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- text/plain

## Responses

200

response body for entity array ProjectActivityClassVal [inline response 200](#)

202

Accepted [String](#)

204

No Content [String](#)

403

Forbidden [String](#)

404

Not found [String](#)

## POST /ActivityClassValues

Add new entity to ActivityClassValues ( [activityClassValuesPost](#))

## Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

## Request body

body [ProjectActivityClassVal-Insert](#) (optional)

*Body Parameter* – request body for inserting entity type ProjectActivityClassVal

## Request headers

## Return type

## [ProjectActivityClassVal](#)

### Example data

Content-Type: application/json

```
{
  "Validity" : "Global",
  "Objgrants" : "It is a Text",
  "Description" : "It is a Text",
  "BlockedForUse" : true,
  "ETag" : "It is a Text",
  "Value" : "It is a Text",
  "ActivityClassSeq" : 1,
  "keyref" : "It is a Text",
  "luname" : "It is a Text",
  "ActivityClassId" : "It is a Text"
}
```

### Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- text/plain

### Responses

201

response body for entity type ProjectActivityClassVal [ProjectActivityClassVal](#)

202

Accepted [String](#)

204

No Content [String](#)

403

Forbidden [String](#)

404

Not found [String](#)

## ProjectActivityClassVal

```
GET /ActivityClassValues/IfsApp.ActivityClassValService.ProjectActivityClassVal.Default
```

Invoke function Default (activityClassValuesIfsAppActivityClassValServiceProjectActivityClassValDefaultGet)

### Request headers

### Query parameters

**\$select (optional)**

*Query Parameter* – Order items by property values, see [http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec\\_SystemQueryOptionorderby](http://docs.oasis-open.org/odata/odata/v4.01/odata-v4.01-part1-protocol.html#sec_SystemQueryOptionorderby)>OData Sorting</a>

### Return type

[ProjectActivityClassVal](#)

### Example data

Content-Type: application/json

```
{
  "Validity" : "Global",
  "Objgrants" : "It is a Text",
  "Description" : "It is a Text",
  "BlockedForUse" : true,
  "ETag" : "It is a Text",
  "Value" : "It is a Text",
  "ActivityClassSeq" : 1,
  "keyref" : "It is a Text",
  "luname" : "It is a Text",
  "ActivityClassId" : "It is a Text"
}
```

### Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json
- text/plain

### Responses

200

response body for function Default [ProjectActivityClassVal](#)

202

Accepted [String](#)

204

No Content [String](#)

403

Forbidden [String](#)

404

Not found [String](#)

## Models

[ [Jump to Methods](#) ]

### Table of Contents

1. [ActClassValidityType\\_Enumeration](#)
2. [ConfigEntityDec](#)

3. [EntityDec](#)
4. [FndBoolean\\_Enumeration](#)
5. [FndDynamicAssistSetup](#)
6. [FndDynamicAssistStep](#)
7. [FndDynamicCommandDef](#)
8. [FndDynamicNextStep](#)
9. [ProjectActivityClassVal](#)
10. [ProjectActivityClassVal-Insert - ProjectActivityClassVal for insert](#)
11. [ProjectActivityClassVal-Update - ProjectActivityClassVal for create](#)
12. [StreamInfoRec](#)
13. [inline\\_response\\_200](#)

**ActClassValidityType\_Enumeration**

[Up](#)

**ConfigEntityDec**

[Up](#)

**ETag (optional)**

[String](#)

example: It is a Text

**Info (optional)**

[String](#)

example: It is a Text

**Attr (optional)**

[String](#)

example: It is a Text

**EntityDec**

[Up](#)

**ETag (optional)**

[String](#)

example: It is a Text

**Info (optional)**

[String](#)

example: It is a Text

**Attr (optional)**

[String](#)

example: It is a Text

**FndBoolean\_Enumeration**

[Up](#)

**FndDynamicAssistSetup**

[Up](#)

**Label (optional)**

[String](#)

example: It is a Text

**Description (optional)**

[String](#)

example: It is a Text

**Entity (optional)**

[String](#)

example: It is a Text

**InitMetaFunction (optional)**

[String](#)

example: It is a Text

**StepsMetaFunction (optional)**

[String](#)

example: It is a Text

**FinishMetaFunction (optional)**

[String](#)

example: It is a Text

**NextStepFunction (optional)**

[String](#)

example: It is a Text

**NumberOfSteps (optional)**

[BigDecimal](#)

example: 1

**StartStep (optional)**

[BigDecimal](#)

example: 1

**FndDynamicAssistStep**

[Up](#)

**Label (optional)**

[String](#)

example: It is a Text

**StepLabel (optional)**

[String](#)

example: It is a Text

**Entity (optional)**

[String](#)

example: It is a Text

**Description (optional)**

[String](#)

example: It is a Text

**Name (optional)**

[String](#)

example: It is a Text

**Datatype (optional)**

[String](#)

example: It is a Text

**ControlType (optional)**

[String](#)

example: It is a Text

**MultiLine (optional)**

[Boolean](#)

example: true

**BindAttribute (optional)**

[String](#)

example: It is a Text

**BindAttributeLabel (optional)**

[String](#)

example: It is a Text

**SaveAction (optional)**

[String](#)

example: It is a Text

**SaveActionParameters (optional)**

[String](#)

example: It is a Text

**ProjectionName (optional)**

[String](#)

example: It is a Text

**DefaultValue (optional)**

[String](#)

example: It is a Text

**Required (optional)**

[Boolean](#)

example: true

**Enumeration (optional)**

[String](#)

example: It is a Text

**Reference (optional)**

[String](#)

example: It is a Text

**Visible (optional)**

[Boolean](#)

example: true

**Enabled (optional)**

[Boolean](#)

example: true

**RemarkNeeded (optional)**

[Boolean](#)

example: true

**RemarkAttribute (optional)**

[String](#)

example: It is a Text

**RemarkAttributeLabel (optional)**

[String](#)

example: It is a Text

**TerminateAllowed (optional)**

[Boolean](#)

example: true

**DynamicLovOptions (optional)**

[String](#)

example: It is a Text

**FinishEnabled (optional)**

[Boolean](#)

example: true

**Editable (optional)**

[Boolean](#)

example: true

**DefaultClobValue (optional)**

[String](#)

**BlobUploadCommand (optional)**

[String](#)

example: It is a Text

**PreviousStepAction (optional)**

[String](#)

example: It is a Text

**PreviousActionParameters (optional)**

[String](#)

example: It is a Text

**Method (optional)**

[String](#)

*example: It is a Text*

**ArgName (optional)**

[String](#)

*example: It is a Text*

**ArgValue (optional)**

[String](#)

*example: It is a Text*

**Result (optional)**

[String](#)

*example: It is a Text*

**Assign (optional)**

[String](#)

*example: It is a Text*

**Next (optional)**

[String](#)

*example: It is a Text*

**Baund (optional)**

[Boolean](#)

*example: true*

**Name (optional)**

[String](#)

*example: It is a Text*

**Projection (optional)**

[String](#)

*example: It is a Text*

**Params (optional)**

[String](#)

*example: It is a Text*

#### **FndDynamicNextStep**

[Up](#)

**NextStep (optional)**

[BigDecimal](#)

*example: 1*

**DefaultValue (optional)**

[String](#)

*example: It is a Text*

**TerminateInfo (optional)**

[String](#)

*example: It is a Text*

#### **ProjectActivityClassVal**

[Up](#)

**ETag (optional)**

[String](#)

*example: It is a Text*

**luname (optional)**

[String](#)

*example: It is a Text*

**keyref (optional)**

[String](#)

*example: It is a Text*

**Objgrants (optional)**

[String](#)

*example: It is a Text*

**ActivityClassSeq (optional)**

[BigDecimal](#)

*example: 1*

**Value (optional)**

[String](#)

*example: It is a Text*

**Description (optional)**

[String](#)

*example: It is a Text*

**BlockedForUse (optional)**

[Boolean](#)

*example: true*

**ActivityClassId (optional)**

[String](#)

*example: It is a Text*

**Validity (optional)**

[ActClassValidityType\\_Enumeration](#)

#### **ProjectActivityClassVal-Insert - ProjectActivityClassVal for insert**

[Up](#)

**ActivityClassSeq (optional)**

[BigDecimal](#)

*example: 1*

**Value (optional)**

[String](#)

*example: It is a Text*

Description (optional)

[String](#)

*example: It is a Text*

BlockedForUse (optional)

[Boolean](#)

*example: true*

ActivityClassId (optional)

[String](#)

*example: It is a Text*

Validity (optional)

[ActClassValidityType\\_Enumeration](#)

**ProjectActivityClassVal-Update - ProjectActivityClassVal for create**

[Up](#)

Description (optional)

[String](#)

*example: It is a Text*

BlockedForUse (optional)

[Boolean](#)

*example: true*

ActivityClassId (optional)

[String](#)

*example: It is a Text*

Validity (optional)

[ActClassValidityType\\_Enumeration](#)

**StreamInfoRec**

[Up](#)

FileName (optional)

[String](#)

*example: It is a Text*

MimeType (optional)

[String](#)

*example: It is a Text*

**inline\_response\_200**

[Up](#)

value (optional)

[array\[ProjectActivityClassVal\]](#)